

USE ON
CONCRETE
BRICK
STONE
BLOCK
STUCCO
WOOD

GRAFFITI BLOCK! 1

EASY TO USE

WATER BASED
LOW ODOR
LONG LASTING
EFFECTIVE
SAFE TO USE
NOT SHINY

**Invisible, Non-gloss Sacrificial
Barrier. Use after graffiti removal
to protect against further damage.**

Shake well before use. Apply with roller, brush, lambswool or low pressure sprayer. Lay down a smooth uniform coating. Avoid gaps. If only protecting a portion of a wall, use a grout joint between bricks as the edge to minimize any slight change in appearance from the coating. Do not apply if freezing temperatures are expected before product can dry. Dries in 1/2 - 3 hours, cures in 24 hours.

When hit with graffiti, remove as soon as possible to prevent subsequent "me-to"

Attacks. Remove only the attacked area with high pressure, hot water at 2000 psi, 4 GPM and 190°F. Make sure the wall can handle high pressure water. Work from bottom up. Otherwise, apply our *HEAVY DUTY CLEANER* or *GRAFFITI-GONE!*, allow to soak 5 minutes and rinse with hose. Recoat to protect wall again.

Protect adjacent areas and yourself. Use between 40°F and 95°F for best results. Expect up to 400 sq. ft./gallon. Rougher areas use more product.

CAUTION: Contains polymers and surfactants. Protect skin, eyes and mouth.
Keep out of reach of children. Do not use on horizontal surfaces.

MULTI-SEAL PACIFIC CORP. ALHAMBRA, CA 91803